

ALPHA 7200 IP67 (Green/Red/Amber)



Photo: ALPHA 7200 IP67 (Green/Red/Amber)

DISPLAY

Display dimensions	h = 183 mm x w = 1524 mm
Pixels	Rows = 24 x columns = 200
Pitch	7,6 mm
Lines per display	1, 2 or 3 lines
Characters per line	20 (1 line) / 33 (2 lines) / 33 (3 lines)
Character height	183 mm / 76 mm / 53 mm
Color	Red - Green - Amber
Brightness	250 nits
Graphics	Red - Green - Amber bmp files
Player	AlphaNET / Alpha protocol

CASE

Case	IP67 black steel
Indoor or outdoor installation	Indoor installation
Case dimensions	h = 348 mm x w = 1682 mm x d = 150 mm
Operating temperature	0°C - 49°C
Humidity	0 % - 95 % non-condensing
Front lens	Polycarbonate
Weight	36,3 kg
Power / consumption	100 - 264 VAC / 47 - 63 Hz / 180 watt

ALPHA 7000 IP67 (Green/Red/Amber)

SOFTWARE / MEMORY / COMMUNICATION

PC Software (Windows)	AlphaNET
Communication	RS232 / RS485 / Ethernet (option)
Memory	80 messages with AlphaNET
Real-Time clock for time and date (RTC)	Included
Mounting system	Wall and ceiling mounting brackets included

The Alpha 7000 Series IP67 displays are designed to increase safety in the workplace, encourage quality control and provide the real-time communication to your employees that is necessary to keep production running.

The IP67 case of the Alpha 7000 displays provides full protection against flying dust, splashing water or direct spraying with water in your production environment.

The displays can be controlled individually or in groups via ethernet, individual serial RS-232 communication or a serial RS-485 network.

Daylight bv since 1991
Brusselsesteenweg 715
B-9050 GENT
BELGIUM
Tel +32 9 230 54 00
Email general: info@daylight.be

BTW BE 0443.834.881
RPR Gent 0443.834.881
REG.NR. 06.26.1.1
Email sales: sales@daylight.be
Email renting: sales@daylight.be
Email support: support@daylight.be

daylight.net
daylight.be
daylight.nl
daylight.lu
daylightdisplay.com
andon.be